

Delivery Premium Quality Fans Globally for Healthier Breathing

World's Largest Selection of Fan Products  
World's Most Comprehensive Fan Solutions



Ningbo Longwell Electric Technology Co., Ltd

Headquarter: NO.100, South of Xuxiang River, Yuyao, Zhejiang Province, China 315400

Tell: +86 574 6218 9863

Fax: +86 574 6218 9863

Phone: 0086 183 5827 4663

Web: [www.longwellfans.com](http://www.longwellfans.com) | [www.longwell-group.com](http://www.longwell-group.com) | [www.longwell-media.com](http://www.longwell-media.com)

Email: [sales@zjlongwell.com](mailto:sales@zjlongwell.com)



**Professional HVAC Fan  
& Motors Manufacturer**

AC Mixed Inline Duct Fan

Ningbo Longwell Electric Technology Co., Ltd



## CATALOGUE

01-02	About Longwell
03-04	Testing and Standards
05-06	Mainly Application
07	Type Code
08-24	AC Mixed Inline Duct Fan



# About Longwell

Born for High-Quality Breathing, LONGWELL Fans Power Your Equipment

OEM for Well-Known Brands

Supplies Fortune 500 Companies

Global Technical Support

LONGWELL is a leading fan manufacturer, specializing in high-quality fans, blowers, motors, and components for heating, ventilation, air conditioning, and refrigeration applications. We have a strong presence in delivery capabilities, design and R&D capabilities, as well as manufacturing, placing us at the forefront of the industry.

Our product range includes EC/DC/AC centrifugal fans, axial fans, AC/BLDC cross-flow fans, single/double forward curved fans, AC/BLDC/ECM motors, and industrial fan blowers. Since our establishment in 1990, we have continuously upgraded our facilities and production capacity, boasting advanced testing labs and production facilities with an annual capacity of millions of fans. With over 20 years of experience, we are highly skilled in the design, development, and manufacture of fans and motors. We export to over 30 countries and serve numerous Fortune 500 clients.

Our facilities and products are compliant with certifications such as ISO9001, ISO14001, BSCI, CE, UL/ETL, CCC, EMC, and LVD. These certifications demonstrate our compliance in quality management, environmental management, social responsibility, and product safety. We are quality-oriented and dedicated to providing products and services that meet international standards.



Equipped with advanced testing labs and production facilities, including a B&K noise lab, CFD simulation lab, air dynamics test chambers, automatic welding machines, CNC machining centers, and auto robot injection machines, we ensure efficient production and on-time delivery.

As industry leaders, we prioritize technological innovation and efficiency. We employ advanced technologies such as aerodynamics principles and CFD simulation to ensure precise and efficient fan designs. Additionally, we offer customized services to design and manufacture fan systems according to specific customer requirements. Our focus is on providing high-tech, high-efficiency products that meet our customers' needs and contribute to a better future.

At LONGWELL, innovation is at the core of our operations, driving continuous improvement. With our extensive experience and expertise, we can quickly customize solutions that meet customer needs. We emphasize technological sophistication, utilizing advanced technologies and high-performance materials to deliver products that are efficient, safe, and reliable. Our brand is widely recognized globally, and we are committed to promoting sustainable development and advancing the efficient fan industry.

LONGWELL looks forward to collaborating with you and providing high-quality customized fan and motor solutions. Please feel free to contact us as we work together to create a brighter future.

193

Staff

40000m<sup>2</sup>

Floor Space

500<sup>+</sup>

Branding Clients

1 Million<sup>+</sup> PCS

Annual Outputs

6

Overseas offices on spot support

50<sup>+</sup>

Members R&D Team



B&K Noise Testing Lab



Production Line



Automatic Welding



Balance Machine



Automatic Welding Machine



Production Line - Centrifugal Fan



Automatic CNC machine



Air Dynamic Test Lab



Production Line - Axial Fans




Production Line

# Testing and Standards

- ISO GB/T 19001-2016 idt ISO 9001:2015/GB/T 24001-2016 idt ISO 14001:2015/GB/T 45001-2020 idt ISO 45001:2018
- UL 507:2017 Ed.10+R:27/CSA C22.2#113:2018 Ed.11
- BSCI ANSI C63.4:2014/ANSI C63.4a-2017
- EN IEC 55014-1:2021/EN IEC 55014-2:2021/EN IEC 61000-3-2:2019 +A1:2021  
EN 61000-3-3:2013 +A1:2019 +A2:2021 +AC:2022-01  
EN 60335-2-80:2003 +A1:2004 +A2:2009;  
EN 60335-1:2012 +A11:2014 +A13:2017 +A1:2019+A14:2019 +A2:2019+A15:2021  
EN 62321-1:2013/EN 62321-2:2014/EN 62321-3-1:2014  
EN 62321-4:2014+A1:2017/EN 62321-5:2014/EN 62321-6:2015  
EN 62321-7-1:2015/EN 62321-7-2:2017/EN 62321-8:2017



Enterprise Credit Evaluation Certificate - Highest Level in China



# Mainly Application

Building ventilation system/Primary air system/  
Bathroom ventilation/Kitchen ventilation/Air conditioning vent



**Grow Tent**



**Bathroom Ventilation**



**Primary Air System**




**Kitchen Ventilation**



**Air Conditioning Vent**

# Type Code

LW D A - 100(4") S - P W N - 02




# AC Mixed Inline Duct Fan

Professional HVAC Fan & Motors Manufacturer



# LWDA-100(4") Series




## Product Characteristic

- Material : Plastic
- Voltage: AC Technology
- Type of Protection: IP54
- Mode of Operation: S1
- Working Temp: 60°C
- Speed Control Type: Constant Speed




## Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Maximum Flow Value (CFM)	Working Power (W)	Speed (RPM)	Noise [dB(A)]
LWDA-100(4")U-PWN-01	110-120	60	410	41	3350	52



# LWDA-100(4") Series




## Product Characteristic

- Material : Plastic
- Voltage: AC Technology
- Type of Protection: IP54
- Mode of Operation: S1
- Working Temp: 60°C
- Speed Control Type: Constant Speed




## Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Maximum Flow Value (CMH)	Working Power (W)	Speed (RPM)	Noise [dB(A)]
LWDA-100(4")S-PWN-02	220-240	50/60	605	41	2900	51



# LWDA-125(5") Series




## Product Characteristic

- Material : Plastic
- Type of Protection: IP54
- Working Temp: 60 °C
- Voltage: AC Technology
- Mode of Operation: S1
- Speed Control Type: Constant Speed




## Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Maximum Flow Value (CFM)	Working Power (W)	Speed (RPM)	Noise [dB(A)]
LWDA-125(5")U-PWN-01	110-120	60	410	41	3350	52



# LWDA-125(5") Series




## Product Characteristic

- Material : Plastic
- Type of Protection: IP54
- Working Temp: 60 °C
- Voltage: AC Technology
- Mode of Operation: S1
- Speed Control Type: Constant Speed




## Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Maximum Flow Value (CMH)	Working Power (W)	Speed (RPM)	Noise [dB(A)]
LWDA-125(5")S-PWN-02	220-240	50/60	605	41	2900	51



# LWDA-150(6") Series




## Product Characteristic

- Material : Metal
- Voltage: AC Technology
- Type of Protection: IP54
- Mode of Operation: S1
- Working Temp: 60°C
- Speed Control Type: Constant Speed




## Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Maximum Flow Value (CFM)	Working Power (W)	Speed (RPM)	Noise [dB(A)]
LWDA-150(6")U-MWN-01	110-120	60	437	55	3400	58



# LWDA-150(6") Series




## Product Characteristic

- Material : Metal
- Voltage: AC Technology
- Type of Protection: IP54
- Mode of Operation: S1
- Working Temp: 60°C
- Speed Control Type: Constant Speed




## Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Maximum Flow Value (CMH)	Working Power (W)	Speed (RPM)	Noise [dB(A)]
LWDA-150(6")S-MWN-02	220-240	50	620	41	2900	55



# LWDA-200(8") Series




## Product Characteristic

- Material : Metal
- Voltage: AC Technology
- Type of Protection: IP54
- Mode of Operation: S1
- Working Temp: 60 °C
- Speed Control Type: Constant Speed




## Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Maximum Flow Value (CFM)	Working Power (W)	Speed (RPM)	Noise [dB(A)]
LWDA-200(8")U-MWN-01	110-120	60	720	179	3400	65



# LWDA-200(8") Series




## Product Characteristic

- Material : Metal
- Voltage: AC Technology
- Type of Protection: IP54
- Mode of Operation: S1
- Working Temp: 60 °C
- Speed Control Type: Constant Speed




## Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Maximum Flow Value (CMH)	Working Power (W)	Speed (RPM)	Noise [dB(A)]
LWDA-200(8")S-MWN-02	220-240	50	1150	143	2900	59



# LWDA-250(10") Series




## Product Characteristic

- Material : Metal
- Voltage: AC Technology
- Type of Protection: IP54
- Mode of Operation: S1
- Working Temp: 60°C
- Speed Control Type: Constant Speed




## Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Maximum Flow Value (CFM)	Working Power (W)	Speed (RPM)	Noise [dB(A)]
LWDA-250(10")U-MWN-01	110-120	60	1219	228	3000	69



# LWDA-250(10") Series




## Product Characteristic

- Material : Metal
- Voltage: AC Technology
- Type of Protection: IP54
- Mode of Operation: S1
- Working Temp: 60°C
- Speed Control Type: Constant Speed




## Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Maximum Flow Value (CMH)	Working Power (W)	Speed (RPM)	Noise [dB(A)]
LWDA-250(10")S-MWN-02	220-240	50	1900	162	2750	68



# LWDA-300(12") Series




## Product Characteristic

- Material : Metal
- Voltage: AC Technology
- Type of Protection: IP54
- Mode of Operation: S1
- Working Temp: 60°C
- Speed Control Type: Constant Speed




## Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Maximum Flow Value (CFM)	Working Power (W)	Speed (RPM)	Noise [dB(A)]
LWDA-300(12")U-MWN-01	110-120	60	1900	489	3450	78



# LWDA-300(12") Series




## Product Characteristic

- Material : Metal
- Voltage: AC Technology
- Type of Protection: IP54
- Mode of Operation: S1
- Working Temp: 60°C
- Speed Control Type: Constant Speed




## Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Maximum Flow Value (CMH)	Working Power (W)	Speed (RPM)	Noise [dB(A)]
LWDA-300(12")S-MWN-02	220-240	50	3150	320	2900	72



# LWDA-350(14") Series




## Product Characteristic

- Material : Metal
- Voltage: AC Technology
- Type of Protection: IP54
- Mode of Operation: S1
- Working Temp: 80 °C
- Speed Control Type: Constant Speed




## Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Maximum Flow Value (CFM)	Working Power (W)	Speed (RPM)	Noise [dB(A)]
LWDA-350(14")U-MWN-01	110-120	60	2130	260	1720	74



# LWDA-350(14") Series




## Product Characteristic

- Material : Metal
- Voltage: AC Technology
- Type of Protection: IP54
- Mode of Operation: S1
- Working Temp: 80 °C
- Speed Control Type: Constant Speed




## Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Maximum Flow Value (CMH)	Working Power (W)	Speed (RPM)	Noise [dB(A)]
LWDA-350(14")S-MWN-02	220-240	50	6450	903	2900	79



# LWDA-400(16") Series





## Product Characteristic

- Material : Metal
- Voltage: AC Technology
- Type of Protection: IP54
- Mode of Operation: S1
- Working Temp: 80 °C
- Speed Control Type: Constant Speed




## Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Maximum Flow Value (CFM)	Working Power (W)	Speed (RPM)	Noise [dB(A)]
LWDA-400(16")U-MWN-01	110-120	60	2500	440	1780	75



# LWDA-400(16") Series



## Product Characteristic

- Material : Metal
- Voltage: AC Technology
- Type of Protection: IP54
- Mode of Operation: S1
- Working Temp: 80 °C
- Speed Control Type: Constant Speed



## Technical Specifications

Model	Voltage (V)	Frequency (Hz)	Maximum Flow Value (CMH)	Working Power (W)	Speed (RPM)	Noise [dB(A)]
LWDA-400(16")S-MWN-02	220-240	50	7100	1300	2940	83

